




## **HOSHIZAKI**











ITEM	HOSHIZAKI CUBELET ICE MAKER
MODEL	CM-50KE-HC
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.45kVA (1.9A)
AMPERAGE	1.5A Starting: 5.4A
ELECTRIC CONSUMPTION	270W (Power Factor: 80%)
ICE PRODUCTION PER 24h	Approx. 55kg (AT. 10°C, WT. 10°C) Approx. 50kg (AT. 21°C, WT. 15°C) Approx. 45kg (AT. 32°C, WT. 21°C)
SHAPE OF ICE	CUBELET
MAX. STORAGE CAPACITY	Approx. 18kg – Leveled (Bin Control Setting Approx. 11kg)
WATER CONSUMPTION PER 24h	Approx. 0.055m³ (AT. 10°C, WT. 10°C) Approx. 0.050m³ (AT. 21°C, WT. 15°C) Approx. 0.045m³ (AT. 32°C, WT. 21°C)
OUTSIDE DIMENSIONS	498mm (W) x 570mm (D) x 697mm (H)
INSULATION FOAM BLOWING AGENT	HFC Free
HEAT REJECTION	, ,
CABINET	Stainless Steel, Galvanized Steel (Rear)
ICE MAKING SYSTEM	<u> </u>
WATER SUPPLY SYSTEM	, , , , ,
DRAIN SYSTEM	Outlet: 24DIA Push Fitting
COMPRESSOR	Hermetic
CONDENSER	Fin and Tube type, Air — cooled
EVAPORATOR	Tube coiled around Cylinder (Solder Plated)
REFRIGERANT	R290 / 509
BIN CONTROL	Actuator and Reed Switch (Time delay controlled)
ICEMAKING WATER CONTROL	Float Switch and Solenoid Valve
ELECTRICAL CIRCUIT PROTECTION	6A Circuit Breaker
REFRIGERANT CIRCUIT PROTECTION	Compressor Internal Thermostat Pressure Switch (Auto — reset)
MECHANISM PROTECTION	Micro switch (Manual — reset)
INTERLOCK	Shutdown by Microprocessor (Manual — reset)
WEIGHT	49kg (Gross 58kg)
WEIGHT	
PACKAGE	Carton 595mm (W) x 680mm (D) x 873mm (H)
	Carton 595mm (W) x 680mm (D) x 873mm (H) Scoop, Installation Kit Ambient Temp. : 5 - 40°C, Water Supply Temp. : 5 - 35°C

- 1. Install the ice maker properly in accordance with the instructions on location, water supply / drain connections and electrical connections stated in the instruction and installation manuals provided.
- 2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.
- 3. Product Code: F161-C103