




PACKAGE	Carton 710mm(W) x 715mm(D) x 996mm(H)	ITEM	Hoshizaki Crescent Ice Maker (Self-Contained Type)
ACCESSORIES	Instruction Manual, Scoop, Leg	MODEL	KM-60C-HC
OPTION	UV-LED, Fully Automated Cleaning kit	POWER SUPPLY	1 PHASE 220 - 240V 50Hz Capacity: Min. 0.56kVA (2.4A)
	Ambient Temp.: 7-38°C, Water Supply Temp.: 7-32°C	AMPERAGE	1.6A(AT. 32°C, WT. 21°C) Starting: 8.5A
OPERATION CONDITION	Water Supply Pressure: 0.07-0.8MPa(0.7-8bar)	ELECTRIC CONSUMPTION	Rated Motor: 255W (Power factor: 63%)
	Voltage Range: ±6%	ICE PRODUCTION PER 24h	Approx. 60kg/d(AT. 10°C, WT. 10°C) Approx. 52kg/d(AT. 21°C, WT. 15°C) Approx. 37kg/d(AT. 32°C, WT. 21°C)
*We reserve the right to make changes in specifications and design without prior notice.		WATER CONSUMPTION PER 24h	Approx. 0.37m³/d(AT. 10°C, WT. 10°C) Approx. 0.14m³/d(AT. 21°C, WT. 15°C) Approx. 0.011m³/d(AT. 32°C, WT. 21°C)
		ELECTRIC CONSUMPTION PER 100kg ICE	14.8kWh/100kg(AT.32°C,WT.21°C)
1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.		WATER CONSUMPTION PER 100kg ICE	0.27m³ /100kg(AT.32°C,WT.21°C)
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.		SHAPE OF ICE	Crescent Cube
3. Standard Model Product Code: F159-C141		FREEZE CYCLE TIME	Approx. 26Min(AT. 21°C, WT. 15°C)
4. Fully Automated Cleaning Model Model: KM-60C-HC-W Product Code: F159-C241		ICE PRODUCTION PER CYCLE	Approx. 0.96kg / 110pcs(AT. 21°C, WT. 15°C)
WEIGHT : 47kg(Gross 59kg)		MAX STORAGE CAPACITY	Approx. 23kg(Bin Cont Setting Approx. 19kg)
		OUTSIDE DIMENSIONS	605mm(W) x 610mm(D) x 988(982-1005)mm(H)
		EXTERIOR	Stainless Steel, Galvanized Steel(Rear),Plastic(Louver)
		INSULATION	Polyurethane Foam
		INSULATION FOAM BLOWING AGENT	Cyclopentane
		CONNECTIONS-ELECTRIC	X-type Connection(with Plug)
		CONNECTIONS-WATER SUPPLY	Inlet G3/4"(connected at rear side)
		CONNECTIONS-DRAIN	Outlet φ 24.5(connected at rear side)
		ICE MAKING SYSTEM	Vertical Evaporator with water flow on both sides
		HARVESTING SYSTEM	Water Supply Harvest Cycle and Hot Gas Defrost
		COMPRESSOR	Hermetic
		CONDENSER	Air-cooled, Fin and Tube type
		HEAT REJECTION	720W(619kcal/h) (AT.32°C, WT.21°C)
		EVAPORATOR	Vertical type, Stainless Steel and Copper
		REFRIGERANT CONTROL	Capillary Tube
		REFRIGERANT CHARGE	R290/90g
		ICE MAKING CONTROL SYSTEM	Float Switch
		HARVESTING CONTROL SYSTEM	Hot Gas and Water, Thermistor and Timer
		ICE MAKING WATER CONTROL SYSTEM	Timer Controlled, Overflow Pipe
		BIN CONTROL SYSTEM	Mechanical Level Switch with Delay
		ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse
		COMPRESSOR PROTECTION	Auto-reset Overload Protector(Internal)
		LOW WATER PROTECTION	Float Switch
		ICE MAKER PROTECTION	Interlock by Controller Board
		WEIGHT	45kg(Gross 57kg)